

### Скрутки цилиндрических (PC) и червячных (IRW) редукторов



Тип	P2 (мм)	D2 (мм)	P1 (мм)	D1 (мм)	A (мм)	Фланцы входные
PC63	105	11	140	11	47	63B5
PC71	120	14	160	14	57	71B5
PC80	160	19	200	19	74	80B5
PC90	160	24	200	24	74	90B5

Цилиндрические Червячные	PC63				PC71				PC80				PC90			
	Фл. вх.	140 мм (63B5)				160 мм (71B5)				200 мм (80B5)				200 мм (90B5)		
Фл. вых.	105 мм (71B14)				120 мм (80B14)				160 мм (100/112B14)				160 мм (100/112B14)			
i	2,76				2,76				2,8				2,45			
IRW040	25	с проставкой 11/14				без проставки				---						
	30									---						
	40									---						
	50	без проставки				---				---						
	60									---						
	80									---						
	100									---						
IRW050	25	с проставкой 11/19				с проставкой 14/19				без проставки						
	30									---						
	40									---						
	50	с проставкой 11/14				без проставки				---						
	60									---						
	80									---						
100	---				---											
IRW063	25	с проставкой 11/24				с проставкой 14/24				с проставкой 19/24						
	30									---						
	40									---						
	50	с проставкой 11/19				с проставкой 14/19				без проставки						
	60									---						
	80									---						
100	---				---											
IRW075	25	с проставкой 11/24				с проставкой 14/24				с проставкой 19/24						
	30									---						
	40									---						
	50	с проставкой 11/19				с проставкой 14/19				без проставки						
	60									---						
	80									---						
100	---				---											
IRW090	25	---				с проставкой 14/28				с проставкой 19/28						
	30	---														
	40	---				с проставкой 14/24				с проставкой 19/24						
	50	---														
	60	---				с проставкой 14/19				без проставки						
	80	---														
100	---				---											
IRW110	25	---				---				с проставкой 19/28						
	30	---														
	40	---														
	50	---				---										
	60	---				---										
	80	---				с проставкой 19/24				с проставкой 24/28						
100	---															
IRW130	25	---				---				---						
	30	---				---				---						
	40	---				---				---						
	50	---				---				---						
	60	---				---				---						
	80	---				с проставкой 19/28				с проставкой 24/28						
100	---															